


High pressure hoses per metre


2SN blue - wrapped cover



Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Non Marking (soot free). Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as self service car wash, swimming baths, offices and plants being equipped with e.g. tiles or special flooring.

R+M Nr.	TYP	DN	∅	P	BP	°C
302 95	2SN	12	22,2	300 bar	≥1200 bar	-40 °C - +150 °C

2SN blue - smooth cover




New

Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Non Marking (soot free). Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as self service car wash, swimming baths, offices and plants being equipped with e.g. tiles or special flooring.

R+M Nr.	TYP	DN	∅	P	BP	°C
302 052	2SN	8	16,7	400 bar	≥1600 bar	-40 °C - +150 °C
302 653	2SN	10	18,9	400 bar	≥1600 bar	-40 °C - +150 °C


2SN black - wrapped cover



Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as industrial plants, agriculture, petrol stations etc.

R+M Nr.	TYP	DN	∅	P	BP	°C
301 51	2SN	8	17,3	400 bar	≥1600 bar	-40 °C - +150 °C
302 81	2SN	12	23,0	300 bar	≥1200 bar	-40 °C - +150 °C

2SN black - smooth cover




New

Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as industrial plants, agriculture, petrol stations etc.

R+M Nr.	TYP	DN	∅	P	BP	°C
301 52	2SN	8	16,7	400 bar	≥1600 bar	-40 °C - +150 °C


2SC blue - wrapped cover



Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Non Marking (soot free). Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as self service car wash, swimming baths, offices and plants being equipped with e.g. tiles or special flooring.

R+M Nr.	TYP	DN	∅	P	BP	°C
302 05	2SC	8	15,6	400 bar	≥1600 bar	-40 °C - +150 °C
302 65	2SC	10	17,5	400 bar	≥1600 bar	-40 °C - +150 °C


2SC black - wrapped cover



Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as industrial plants, agriculture, petrol stations etc.

R+M Nr.	TYP	DN	∅	P	BP	°C
301 02	2SC	6	14,0	400 bar	≥1600 bar	-40 °C - +150 °C
301 50	2SC	8	15,6	400 bar	≥1600 bar	-40 °C - +150 °C
302 50	2SC	10	17,5	400 bar	≥1600 bar	-40 °C - +150 °C
302 55	2SC	10	17,5	500 bar	≥1700 bar	-40 °C - +150 °C

2SC grey - wrapped cover



Interior synthetic rubber. Very temperature-resistant. Resistant to usual washing agents. Double wire braid. Surface synthetic rubber. Non Marking (soot free). Abrasion-, oil-, ozone-resistant and weatherproof. **Field of application:** suitable for versatile, universal applications such as self service car wash, swimming baths, offices and plants being equipped with e.g. tiles or special flooring.

R+M Nr.	TYP	DN	∅	P	BP	°C
302 06	2SC	8	15,6	400 bar	≥1600 bar	-40 °C - +150 °C
302 66	2SC	10	17,5	400 bar	≥1600 bar	-40 °C - +150 °C