

Hose tails

Male thread

Brass.
Max. 150 °CStainless steel.
Max. 150 °CPlastic.
Max. 60 °CPlastic.
Max. 60 °CPlastic.
Max. 60 °CBrass.
Max. 150 °C

DN	⊙	R+M Nr.	⊓	R+M Nr.	⊓	R+M Nr.	⊓	R+M Nr.	⊓	R+M Nr.	⊓	⊓	⊓	DN	⊙	R+M Nr.	⊓
4 mm	1/8"			712 05	27									6 mm	1/4"	710 104	33
6 mm	1/8"	710 00	31	712 10	33	713 10	21	714 10	57	21				8 mm	1/4"	710 204	33
6 mm	1/4"	710 10	35	712 20	38	713 20	26	714 20	57	26				8 mm	3/8"	710 504	33
6 mm	3/8"	710 40	36	712 40	39	713 40	26							8 mm	1/2"	710 704	36
6 mm	1/2"	710 65	40											12 mm	3/8"	710 604	40
8 mm	1/8"	710 05	31											12 mm	1/2"	710 804	38
8 mm	1/4"	710 20	34	712 30	41	713 30	28	714 30	66	28							
8 mm	3/8"	710 50	38	712 50	41	713 50	33										
8 mm	1/2"	710 70	49	712 70	49	713 70	37										
10 mm	1/4"	710 25	34			713 32	30										
10 mm	3/8"	710 55	35	712 55	44												
12 mm	1/4"	710 30	35														
12 mm	3/8"	710 60	38	712 60	46	713 60	32										
12 mm	1/2"	710 80	50	712 80	54	713 80	36										
12 mm	3/4"	710 90	47														
16 mm	3/4"	710 95	49														
19 mm	3/4"	711 00	47	712 90	58	713 90	42										
19 mm	1"	711 20	49														
25 mm	1"	711 10	55														

Female thread

Hose connector reduction

Plastic.
Max. 60 °C

DN	R+M Nr.	⊓	⊓
8 mm - 6 mm	717 50	55	27
8 mm - 12 mm	717 60	57	35

2/3 hose tails

Filter



Flat seal

R+M Nr.	⊙
725 40	3/4"

Brass.
Max. 150 °CPlastic.
Max. 60 °CBrass.
Max. 150 °C

DN	⊙	R+M Nr.	⊓	R+M Nr.	⊓	R+M Nr.	⊓	DN	R+M Nr.	⊓	R+M Nr.	⊓	⊓	R+M Nr.	⊓
10 mm	1/2"			711 68	41			6 mm	715 10	49	717 10	50	26	716 10	46
10 mm	3/4"			711 75	41			8 mm	715 20	56	717 20	58	30	716 20	53
13 mm	1/2"	711 52	34					12 mm	715 30	73	717 30	68	36	716 30	68
13 mm	3/4"	711 50	36	711 60	49	711 70	42								
13 mm	1"	711 51	41												
19 mm	3/4"	711 55	39												
19 mm	1"	711 56	38												
25 mm	1"	711 57	40												

Hose clamps



1.4016 stainless steel housing and band. Hexagon screw zinc-plated. Worm gear high tension. Flat tape inner sides with turned up rims. According to DIN 3017, W2

Clamps with hexagon screw

R+M Nr.	VPE	⊘	⊓	R+M Nr.	VPE	⊘	⊓
735 10	1	8 - 12 mm	9 mm	735 10 100	100	8 - 12 mm	9 mm
735 20	1	10 - 16 mm	9 mm	735 20 100	100	10 - 16 mm	9 mm
735 30	1	12 - 20 mm	9 mm	735 30 100	100	12 - 20 mm	9 mm
735 40	1	16 - 25 mm	9 mm	735 40 100	100	16 - 25 mm	9 mm
735 50	1	20 - 32 mm	9 mm	735 50 100	100	20 - 32 mm	9 mm
735 60	1	25 - 40 mm	9 mm	735 60 100	100	25 - 40 mm	9 mm
735 70	1	32 - 50 mm	9 mm	735 70 100	100	32 - 50 mm	9 mm
735 80	1	50 - 70 mm	9 mm	735 80 100	100	50 - 70 mm	9 mm

Clamps with hexagon screw

R+M Nr.	VPE	⊘	⊓
735 10	100	8 - 12 mm	9 mm
735 20	100	10 - 16 mm	9 mm
735 30	100	12 - 20 mm	9 mm
735 40	100	16 - 25 mm	9 mm
735 50	100	20 - 32 mm	9 mm
735 60	100	25 - 40 mm	9 mm
735 70	100	32 - 50 mm	9 mm
735 80	100	50 - 70 mm	9 mm

Symbols ⊕ inlet ⊖ outlet DN nominal diameter ⊘ diameter ⊓ height ⊓ length ⊙ thread VPE packing unit M material TYP type